

TFP-1211/TFP-1212/ TFP-1214

Intelligent Addressable Fire Alarm Panels

Teknim wireless addressable devices are used with Teknim addressable control panels. Wireless addressable systems, designed according to EN54 standards, allow a completely wireless or hybrid system design with existing Teknim addressable control panels. The functions and settings of all wireless devices can be made on the addressable panel.



General Features

- EN 54-2 and EN 54-4 Certified 1,2 and 4 Loop Options
- Wireless Device Support With TWM-1885 Wireless Addressable Coordinator
- 72 Programmable Zones
- Cable Distance Up To 2.5Km Per Loop
- 16 Panel Network Support
- Easy to read, 240*64 Wide LCD Graphic Display and User-friendly Interface
- Storing up to 12.000 Events History

EN 54-2

EN 54-4

Technical Specifications

	TFP-1211	TFP-1212	TFP-1214
Standard		EN54-2, EN54-4	
Display		240x64 Graphic Display	
Loops	1	2	4
Output Power	240	240	127
Number of Devices Supports Per Loop	240	480	508
Number of Zones		72	
Network		16 Panel	
Number of Monitored Siren Outputs		2 Pcs 500mA	
General Error Relay		1x NC/NO 30V 2A	
Fire Alarm Relay		1x NC/NO 30V 2A	
Operating Temperature		-10°C ~ +55°C	
Size (mm)		385 mm x 380 mm	
Humidity		95% RH	
Protection Class		IP30	

